

# SASSO 80 s | k with offset option



SASSO 80 s

SASSO 80 k offset

**D**  
 Strahlerelement aus Aluminium in starrer oder dreh- und schwenkbarer Ausführung  
 Einstellbare Variante 355° dreh-, 35° schwenkbar  
 Offset mit verbesserter Entblendung durch zurückversetztes Strahlerelement  
 Set für randlosen Einbau in Gipskartondecken 8-25mm  
 Einbauring für Zwischendecken von 2-25mm  
 Durch Patentkugelschnapper werkzeuglos einsetzbar  
 Varianten mit LED und Halogen Bestückung erhältlich  
 Inkl. Phasenabschnittsdimmer (trailing-edge), Konverter wahlweise mit DALI Signal

**E**  
 Spotlight made of aluminium in fixed or rotatable and tiltable design  
 Adjustable version 355° rotatable and 35° tiltable  
 Offset with improved glare reduction through offset spotlight  
 Mounting set for trimless installation in plasterboard ceilings 8-25mm  
 Mounting ring for ceilings from 2-25mm  
 Patented ball catch system installs without tools  
 Versions available with LED and halogen lamps  
 Including trailing-edge phase dimmer, converter optional with DALI signal

**F**  
 Spot en aluminium en version fixe ou orientable et inclinable  
 Variante réglable orientable sur 355° et inclinable sur 35°  
 Offset avec anti-éblouissement amélioré par élément rayonnant en retrait  
 Kit montage pr. encastrement sans rebord dans plafond en plaque de plâtre 8-25mm  
 Bague de montage pour faux-plafonds de 2-25mm  
 Installation sans outil grâce à un système breveté de clips à bille  
 Variantes disponibles avec équipement LED et halogène  
 Comprenant variateur fin de phase, convertisseur Dali en option

INSET		SASSO 80 S	
		COB LED 220-240V	<b>TYPE</b> 11W LED   820 lm* 16W LED   1100 lm* 23W LED   1500 lm* <b>CODE</b> 052-0021###F 052-0022###F 052-0023###F
		COB LED 220-240V	<b>SASSO 80 K</b> <b>TYPE</b> 7,5W LED   500 lm* 11W LED   680 lm* 16W LED   860 lm* <b>CS</b> <b>CODE</b> 052-0011### 052-0012### 052-0013###
		QR-CBC51 GUS.3 12V	<b>SASSO 80 K</b> <b>TYPE</b> 1x35W QR-CBC51 <b>CS</b> <b>CODE</b> 052-131301#
		QPAR16 G10 220-240V	<b>SASSO 80 K</b> <b>TYPE</b> 1x35W QPAR16 <b>CS</b> <b>CODE</b> 052-131901#

LED COLOUR TEMPERATURE	
2700K	3000K
052-...4... 2700K 052-...5... 3000K *System power   Luminous flux 3000K	

CONTROL	
non DIM	DIM DALI
052-...1... non DIM / trailing-edge* 052-...8... DIM DALI *except SASSO 80 K   7,5W version	

COLOUR	
052-...7... white 052-...8... black	

REFLECTOR LED	
052-...M... medium 24° 052-...F... flood 40°	

PHOTOMETRIC DATA	
	See page 653 for photometric data

MOUNTING	
	90  1 8-25 ø 86 <b>MOUNTING SET TRIMLESS</b> for installation in plasterboard ceilings <b>TYPE</b> trimless mounting set <b>CS</b> <b>CODE</b> 052-1921310
	92  1 2-25 ø 98 <b>MOUNTING RING WITH TRIM</b> for intermediate ceilings <b>COLOUR</b> white <b>CS</b> black <b>CODE</b> 052-1922317 052-1922318

MOUNTING OFFSET	
	90  H   1 8-25 ø 86 <b>MOUNTING SET OFFSET TRIMLESS</b> for installation in plasterboard ceilings <b>COLOUR</b> white <b>CS</b> <b>H (MM)</b> 15 + H Inset <b>CODE</b> 052-1931317
	92  H   1 2-25 ø 98 <b>MOUNTING RING OFFSET WITH TRIM</b> for intermediate ceilings <b>COLOUR</b> white <b>CS</b> <b>H (MM)</b> 13 + H Inset <b>CODE</b> 052-1932317

SUPPLY	
	<b>ELECTRONIC TRANSFORMER</b> <b>TYPE</b> 70VA/230-240V/12V <b>CS</b> 105VA/230-240V/12V <b>CS</b> 150VA/230-240V/12V 105VA/230-240V/12V DIM DALI <b>CS</b> 150VA/230-240V/12V DIM DALI <b>L/B/H (MM)</b> 102/51/30 102/51/30 206/45/40 167/42/31 207/46/40 <b>CODE</b> 002-70700 002-71000 002-71500 002-71025 002-71515

ACCESSORY	
	<b>MOUNTING HOUSING</b> for exposed concrete <b>TYPE</b> mounting housing <b>CS</b> use not for offset version <b>CODE</b> 060-00080
	<b>MOUNTING HOUSING</b> for primed concrete ceilings <b>TYPE</b> standard w. channel <b>CS</b> use not for LED version <b>L/B/H (MM)</b> 225/225/135 460/225/135 <b>CODE</b> 052-1914310 052-1915310
	<b>SEE PAGE 125 FOR MORE ACCESSORIES</b> Colour and protection filter Lenses and honeycomb louver